

Work Zone Calculated Capacity for 3 lanes/2 lanes open

Climbing Grade (%)	Length (mi)	2	4	5	6	8	10	15	20	25	30	35	40
<2		2860	2860	2860	2860	2860	2860	2860	2860	2844	2783	2723	2667
>2-3	0 - 0.49	2860	2860	2860	2860	2860	2860	2860	2860	2844	2783	2723	2667
	0.5 - 0.74	2860	2860	2860	2860	2860	2860	2860	2860	2844	2783	2723	2667
	0.75 - 1.00	2860	2860	2860	2860	2860	2860	2860	2860	2844	2783	2723	2667
	>1.00	2860	2860	2860	2860	2860	2860	2783	2667	2560	2462	2370	2286
>3-4	0 - 0.49	2860	2860	2860	2860	2860	2860	2860	2860	2844	2783	2723	2667
	0.5 - 0.74	2860	2860	2860	2860	2860	2860	2783	2667	2560	2462	2370	2286
	0.75 - 1.00	2860	2860	2860	2860	2857	2783	2783	2667	2560	2462	2370	2286
	>1.00	2860	2860	2860	2857	2759	2667	2612	2462	2327	2207	2098	2000
>4-5	0 - 0.49	2860	2860	2860	2860	2860	2860	2783	2667	2560	2462	2370	2286
	0.5 - 0.74	2860	2860	2860	2857	2857	2783	2612	2462	2327	2207	2098	2000
	0.75 - 1.00	2860	2860	2844	2783	2759	2667	2462	2286	2133	2000	1882	1778
	>1.00	2860	2857	2783	2712	2667	2560	2462	2286	2133	2000	1882	1778
>5-6	0 - 0.49	2860	2857	2844	2857	2857	2783	2612	2462	2327	2207	2098	2000
	0.5 - 0.74	2860	2807	2783	2783	2759	2667	2462	2286	2133	2000	1882	1778
	0.75 - 1.00	2860	2759	2723	2712	2759	2667	2462	2286	2133	2000	1882	1778
	>1.00	2860	2759	2667	2645	2667	2560	2327	2133	1969	1829	1707	1600
>6	0 - 0.49	2860	2807	2783	2712	2667	2667	2612	2462	2327	2207	2098	2000
	0.5 - 0.74	2860	2759	2723	2645	2581	2560	2462	2286	2133	2000	1882	1778
	0.75 - 1.00	2860	2712	2667	2581	2500	2462	2327	2133	1969	1829	1707	1600
	>1.00	2857	2667	2612	2520	2424	2370	2207	2000	1829	1684	1561	1455