

MAINTENANCE PLANNING GUIDELINES		2006																																																
ACTIVITY: Drainage (R316) MAJOR & MINOR	ACTION: Repair Curbing <i>B. Asphalt Curbs</i>																																																	
DEFINITION: The time and expenses incurred for the installation, repair and maintenance of roadway drainage ditches, structures, and all slide repairs. This includes installing and maintaining pavement drainage systems.																																																		
PURPOSE: To restore drainage by repairing asphalt curbs, islands, and medians.																																																		
SCHEDULING: As needed when the air and ground temperatures are above 60°F.	<table border="1" style="width: 100%; text-align: center;"> <tr> <td>J</td><td>F</td><td>M</td><td>A</td><td>M</td><td>J</td><td>J</td><td>A</td><td>S</td><td>O</td><td>N</td><td>D</td> </tr> <tr> <td>A</td><td>E</td><td>A</td><td>P</td><td>A</td><td>U</td><td>U</td><td>U</td><td>E</td><td>C</td><td>O</td><td>E</td> </tr> <tr> <td>N</td><td>B</td><td>R</td><td>R</td><td>Y</td><td>N</td><td>L</td><td>G</td><td>P</td><td>T</td><td>V</td><td>C</td> </tr> <tr> <td></td><td></td><td></td><td style="background-color: black;"></td><td style="background-color: black;"></td><td style="background-color: black;"></td><td style="background-color: black;"></td><td style="background-color: black;"></td><td style="background-color: black;"></td><td></td><td></td><td></td> </tr> </table>		J	F	M	A	M	J	J	A	S	O	N	D	A	E	A	P	A	U	U	U	E	C	O	E	N	B	R	R	Y	N	L	G	P	T	V	C												
J	F	M	A	M	J	J	A	S	O	N	D																																							
A	E	A	P	A	U	U	U	E	C	O	E																																							
N	B	R	R	Y	N	L	G	P	T	V	C																																							
RECOMMENDED EQUIPMENT: <ul style="list-style-type: none"> • Trucks • Air Compressor/Asphalt Bit • Asphalt Curb Machine • Distributor • Traffic Control Equipment; (See EPG 616.23 Traffic Control for Field Operations) 	RECOMMENDED PROCEDURE: <ol style="list-style-type: none"> 1. Place traffic control devices as needed. 2. Remove damaged material, tack, repair, and compact area. 3. Backfill and seed as necessary. 4. Remove traffic control devices. 																																																	
RECOMMENDED MATERIAL: <ul style="list-style-type: none"> • Hot Mix • Liquid Asphalt (Tacking Grade) • Seed 																																																		
SAFETY: Be careful when working near traffic. Wear all appropriate PPE. Refer to the Safety Policies, Rules & Regulations – Employee Handbook .																																																		
OTHER CONSIDERATIONS: N/A																																																		
REFERENCES: Missouri Standard Specifications for Highway Construction Section; 609.3 .																																																		