

Work Zone Calculated Capacity for 5 lanes/2 lanes open

Climbing Grade (%)	Length (mi)	2	4	5	6	8	10	15	20	25	30	35	40
<2		2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640
>2-3	0 - 0.49	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640
	0.5 - 0.74	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640
	0.75 - 1.00	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640
>3-4	>1.00	2640	2640	2640	2640	2640	2640	2640	2640	2560	2462	2370	2286
	0 - 0.49	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640	2640
	0.5 - 0.74	2640	2640	2640	2640	2640	2640	2640	2640	2560	2462	2370	2286
	0.75 - 1.00	2640	2640	2640	2640	2640	2640	2640	2640	2560	2462	2370	2286
>4-5	>1.00	2640	2640	2640	2640	2640	2640	2612	2462	2327	2207	2098	2000
	0 - 0.49	2640	2640	2640	2640	2640	2640	2640	2640	2560	2462	2370	2286
	0.5 - 0.74	2640	2640	2640	2640	2640	2640	2612	2462	2327	2207	2098	2000
	0.75 - 1.00	2640	2640	2640	2640	2640	2640	2462	2286	2133	2000	1882	1778
>5-6	>1.00	2640	2640	2640	2640	2640	2560	2462	2286	2133	2000	1882	1778
	0 - 0.49	2640	2640	2640	2640	2640	2640	2612	2462	2327	2207	2098	2000
	0.5 - 0.74	2640	2640	2640	2640	2640	2640	2462	2286	2133	2000	1882	1778
	0.75 - 1.00	2640	2640	2640	2640	2640	2640	2462	2286	2133	2000	1882	1778
>6	>1.00	2640	2640	2640	2640	2640	2560	2327	2133	1969	1829	1707	1600
	0 - 0.49	2640	2640	2640	2640	2640	2640	2612	2462	2327	2207	2098	2000
	0.5 - 0.74	2640	2640	2640	2640	2581	2560	2462	2286	2133	2000	1882	1778
	0.75 - 1.00	2640	2640	2640	2581	2500	2462	2327	2133	1969	1829	1707	1600
	>1.00	2640	2640	2612	2520	2424	2370	2207	2000	1829	1684	1561	1455